



C.R. ONSRUD

AMERICAN-MADE CNC MACHINERY

RH-Series Specifications

MODEL NUMBER	145G18R	241G18R	333G18R	98RH18
Number of Axes	3	3	3	3
Table Size	48" X 96"	(2X) 96" X 48"	(2X) 96" X 48"	48" X 96"
Z Clearance	4"	4"	4"	4"
X-Axis Travel	145"	241"	325"	132"
Y-Axis Travel	60"	60"	60"	78"
Z-Axis Travel	11"	11"	11"	11"
Approx. Footprint	16' X 8'	24' X 8'	32' X 8'	30' X 12'
Machining Speed	2500 ipm	2500 ipm	2500 ipm	3600 ipm
X & Y Rapid Traverse	3000 ipm	3000 ipm	3000 ipm	4000 ipm
Standard Spindle	18HP 24,000 rpm	18HP 24,000 rpm	18HP 24,000 rpm	18HP 24,000 rpm
Tool Shank	HSK 63F	HSK 63F	HSK 63F	HSK 63F
Standard Tool Capacity	12	12	12	12
Standard Vacuum Zones	2	2	3	2

All models are available with 73" wide tables instead of standard 61" (footprint increase of 2ft.)



MACHINERY INC.

*SERVING the CAROLINAS
and VIRGINIA
SINCE 1953*