

Machine Features



DRIVE

- Motor: 2/3HP (1PH / 3PH) (120V or 230V) DC Brushless Motor
- Amp Requirement: 110V: 4.6 AMPS, 230V: 1.4 AMPS
- CE Approved Electrical components
- Forward/Reversing Motor



DRIVE

- Variable Speed Range of 8-85fpm



HOLD DOWNS

- (7) 2.3" x 2.3" Non Marking Synthetic Rubber Rollers included
- Each roller equipped with 18mm (3/4") of independent suspension travel for premium part hold.



FULL MOTION STAND

- Tiltable: 90°
- 360° head rotation
- Manual raise
- 7-1/8" vertical travel
- 17" horizontal travel
- Max height parallel to table is 7.1"

Machine Features



- (7) 2.3" x 2.3" non marking synthetic rubber rollers
-



- Head can be turned 90° for vertical part feeding.
-



- Double full rotating couplings for easy head maneuverability.
-



- Full range universal stand allows for infinite stock feeding options.

Machine Features



- Each wheel with its own independent drive shaft for slack free feeding.



- (7) roll design allows for smooth profiled part feeding of smaller parts.

NORTHTECH

Machine, LLC



102 Walnut Street
Borden, IN 47106
(812) 967-7400 Fax (812) 967-7401
www.NorthtechMachine.com info@NorthtechMachine.com