

# INTOREX



**woodworking  
machinery**

## CKI 1500/2500 Specifications

<b>Max. Length to be mechanized</b>	1.500 / 2.500 mm
<b>Max. diameter to be machined</b>	280 mm
<b>Manual feeding up to</b>	Sq. 200 mm
<b>Total axes</b>	4 / 5
<b>Axes stroke</b>	
X axis	160 mm
A axis	160 mm
Z axis	1850 / 2850 mm
C axis	∞
B axis (Optional)	160 mm
<b>Motor Powers</b>	
<b>Headstock (C axis)</b>	12,8 KW
Rotation speed	0 - 5.000 rpm
<b>Copier (B Axis) interchangeable</b>	
Grooving and twisting ( <i>router type tool</i> )	2.2 kw
Tool rotation speed	18.000 rpm
Grooving and twisting ( <i>radial type tool</i> )	3.7 kw
Tool rotation speed	10.000 rpm
Sanding unit with narrow belt.	0.5 Kw
Belt rotation speed	2.750 rpm
<b>Total power installed</b>	27 Kw
<b>Weight of the machine</b>	2.350 / 2.960 kg
<b>Dimensions</b>	3400x4250x1500x2100(h)mm

*INTOREX reserves the right to modify the technical features of its products without prior notice*



**MACHINERY INC.**

*SERVING the CAROLINAS  
and VIRGINIA  
SINCE 1953*