

COMBINE FLEXIBLY – AS YOUR REQUIREMENTS DEMAND.

F2 | F4 | F5



Copyright: Altendorgroup America | 06.2019/200

Specification and options	F2	F4	F5
PLC control with touch screen (10")	●	●	●
Pre-milling aggregate	●	●	●
Top-side fast-heating glue pot (maintenance-free)	●	●	●
Pot interchange mount including adhesive interchanger for PUR processing	●	●	●
Trim saw	●	●	●
Top/bottom trimming	●	●	●
Radius profile scraper*	—	○	●
Multi-radius profile scraper	—	○	○
Corner rounding unit	—	●	●
Surface scraper with dual-tracing	○	●	●
Buffer unit*	—	○	●
Support plate for edge material	●	●	●
Visual display for workpiece sequence	●	●	●
Workpiece support (folds out to front)	●	●	●
Pneumatic roll cutting station (shears-type design, Altendorf system)	●	●	●
Automatic central lubrication (trim saw, corner rounding unit)	—	●	●
Double roller overhead pressure system (ball-bearing mounted)	●	●	●
Conveyor chain with permanently attached special links	●	●	●

● Basic configuration ○ Option — not included

* The F4 can be optionally fitted with a radius profile scraper or a buffer unit. An empty space is also possible.

Further specifications on request. Due to an unknown mains voltage, an adeption transformer must be connected in front of the machine.