

# INTOREX



**woodworking  
machinery**

## CKX 600/1300/1600 Specifications

Max. Length to be mechanized	600 / 1300 / 1600 mm
Max. diameter to be machined	280 mm
Automatic feeding up to	Sq. 100 mm
Manual feeding up to	Sq. 200 mm
Total axes	4 / 5
<b>Axes strokes</b> X axis A axis Z axis C axis B axis (Optional)	160 mm 160 mm 1200 / 1800 / 2400 mm $\infty$ 160 mm
<b>Motor Powers</b>	
Headstock ( <i>C axis</i> ) Rotation speed	12,8 KW 0 - 5.000 rpm
<b>Copier (<i>B Axis</i>) interchangeable</b>	
Grooving and twisting (router type tool) Tool rotation speed	2.2 kw 18.000 rpm
Grooving and twisting (radial type tool) Tool rotation speed	3.7 kw 10.000 rpm
Sanding unit with narrow belt. Belt rotation speed	0.5 Kw 2.750 rpm
<b>Total power installed</b>	27 Kw
<b>Weight of the machine</b>	2.450 / 3.000 / 3.450 kg
<b>Dimensions</b>	2600 / 3400 / 4100x 2200x2590mm

*INTOREX reserves the right to modify the technical features of its products without prior notice*



**MACHINERY INC.**

*SERVING the CAROLINAS  
and VIRGINIA  
SINCE 1953*